

# MATERIAL SAFETY DATA SHEET

MAGNALUBE-G

PTFE/PETROLEUM GREASE

---

MANUFACTURER: SAUNDERS ENTERPRISES, INC. 11-51 44TH ROAD LONG ISLAND CITY, N.Y. 11101	EMERGENCY HEALTH INFORMATION: (718) 729-1000 EMERGENCY SPILL INFORMATION: (718) 729-2628 OTHER PRODUCT SAFETY INFO: (718) 729-2671
--	--

---

COMPOSITION/INFORMATION ON INGREDIENTS	CAS NUMBER	PERCENTAGE
--	------------	------------

---

LUBRICATING BASE OIL SEVERELY REFINED PETROLEUM DISTILLATE ACGIH-TLV-5MG/M CUBEDIOMG/M3 (MIST) ACGIH STEL	* SEE BELOW	78%
---	-------------	-----

ORGANIC POLYUREA THICKENER (TSCA PROPRIETY COMPOUND EPA FILE #26847 NON-HAZARDOUS) PTFE	#9002-84-0	22%
---	------------	-----

\*THE BASE OIL MAY BE A MIXTURE OF ANY OF THE FOLLOWING: CAS 64741884, CAS 6471895, CAS 6471964, CAS 64741975, CAS 64742014, CAS 64742525, CAS 64742536, CAS 64742547, CAS 64742627, CAS 64742650, OR CAS 72623837.

## COMPOSITION COMMENT

ALL THE COMPONENTS OF THIS MATERIAL ARE ON THE TOXIC SUBSTANCES CONTROL ACT CHEMICAL SUBSTANCES INVENTORY.

THIS PRODUCT FITS THE ACGIH DEFINITION FOR MINERAL OIL MIST. THE ACGIH TLV IS 5 MG/M3, THE OSHA PEL IS 5 MG/M3.

## HAZARDS IDENTIFICATION

---

### POTENTIAL HEALTH EFFECTS:

#### EYE:

NOT EXPECTED TO CAUSE PROLONGED OR SIGNIFICANT EYE IRRITATION.

#### SKIN:

CONTACT WITH THE SKIN IS NOT EXPECTED TO CAUSE PROLONGED OR SIGNIFICANT IRRITATION. SKIN CONTACT MAY CAUSE DRYING OR DEFATTING OF THE SKIN. NOT EXPECTED TO BE HARMFUL TO INTERNAL ORGANS IF ABSORBED THROUGH THE SKIN.

#### HIGH-PRESSURE EQUIPMENT INFORMATION:

ACCIDENTAL HIGH-VELOCITY INJECTION UNDER THE SKIN OF MATERIALS OF THIS TYPE MAY RESULT IN SERIOUS INJURY. SEEK MEDICAL ATTENTION AT ONCE SHOULD AN ACCIDENT LIKE THIS OCCUR. THE INITIAL WOUND AT THE INJECTION SITE MAY NOT APPEAR TO BE SERIOUS AT FIRST; BUT, IF LEFT UNTREATED, COULD RESULT IN DISFIGUREMENT OR AMPUTATION OF THE AFFECTED PART.

#### INGESTION:

IF SWALLOWED, THIS SUBSTANCE IS CONSIDERED PRACTICALLY NON-TOXIC TO INTERNAL ORGANS.

#### INHALATION:

NOT EXPECTED TO BE HARMFUL IF INHALED. CONTAINS A PETROLEUM-BASED MINERAL PROLONGED OR REPEATED INHALATION OF OIL MIST AT AIRBORNE LEVELS ABOVE THE RECOMMENDED MINERAL OIL MIST EXPOSURE LIMIT.

#### SIGNS AND SYMPTOMS OF EXPOSURE:

SKIN DEFATTING: MAY INCLUDE DRYING AND REDDENING OF THE SKIN.

## FIRST AID MEASURES

---

EYE:

NO SPECIFIC FIRST AID MEASURES ARE REQUIRED BECAUSE THIS MATERIAL IS NOT EXPECTED TO CAUSE EYE IRRITATION. AS A PRECAUTION REMOVE CONTACT LENSES, IF WORN, AND FLUSH EYES WITH WATER.

SKIN:

REMOVE CONTAMINATED CLOTHING AND SHOES. USE A WATERLESS HAND CLEANER, MINERAL OIL, OR PETROLEUM JELLY TO REMOVE THE MATERIAL THEN WASH SKIN WITH SOAP AND WATER. WASH OR CLEAN CONTAMINATED CLOTHING AND SHOES BEFORE REUSE.

INGESTION:

NO SPECIFIC FIRST AID MEASURES ARE REQUIRED BECAUSE THIS MATERIAL IS NOT EXPECTED TO BE HARMFUL IF SWALLOWED. DO NOT INDUCE VOMITING. AS A PRECAUTION, GIVE THE PERSON A GLASS OF WATER OR MILK TO DRINK AND GET MEDICAL ADVICE. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

INHALATION:

IF EXPOSTED TO EXCESSIVE LEVELS OF MATERIAL IN THE AIR, MOVE THE EXPOSED PERSON TO FRESH AIR. GET MEDICAL ATTENTION IF COUGHING OR RESPIRATORY DISCOMFORT OCCURS.

NOTE TO PHYSICIANS:

IN AN ACCIDENT INVOLVING HIGH-PRESSURE EQUIPMENT, THIS PRODUCT MAY BE INJECTED UNDER THE SKIN. SUCH AN ACCIDENT MAY RESULT IN A SMALL SOMETIMES BLOODLESS, PUNCTURE WOUND. HOWEVER, BECAUSE OF ITS DRIVING FORCE, MATERIAL INJECTED INTO A FINGER TIP CAN BE DEPOSITED INTO THE PALM OF THE HAND. WITHIN 24 HOURS, THERE IS USUALLY A GREAT DEAL OF SWELLING, DISCOLORATION AND INTENSE THROBBING PAIN. IMMEDIATE TREATMENT AT A SURGICAL EMERGENCY CENTER IS RECOMMENDED.

## **FIRE FIGHTING MEASURES**

---

FIRE CLASSIFICATION:

CLASSIFICATION (29 CFR 1910.1200): NOT CLASSIFIED BY OSHA AS FLAMMABLE OR COMBUSTIBLE.

FLAMMABLE PROPERTIES:

FLASH POINT: (CCC) -525F (-273C)

AUTOIGNITION: NDA

FLAMMABILITY LIMITS (% BY VOLUME IN AIR): LOWER. NA UPPER: NA

EXTINGUISHING MEDIA: CO2, DRY CHEMICAL, FOAM ANI) WATER FOG.

NFPA RATINGS: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

FIRE FIGHTING INSTRUCTIONS:

THIS MATERIAL WILL BURN ALTHOUGH IT IS NOT EASILY IGNITED.

COMBUSTION PRODUCTS:

NORMAL COMBUSTION FORMS CARBON DIOXIDE, WATER VAPOR AND MAY PRODUCE OXIDES OF SULFUR, NITROGEN AND PHOSPHORUS. COMBUSTION MAY FORM OXIDES OF CALCIUM AND H2S. INCOMPLETE COMBUSTION CAN PRODUCE CARBON MONOXIDE.

## **ACCIDENTAL RELEASE MEASURES**

---

CLEAN UP SPILLS IMMEDIATELY, OBSERVING PRECAUTIONS IN EXPOSURE CONTROLS/ PERSONAL PROTECTION SECTION.

## **HANDLING AND STORAGE**

---

HANDLING & STORAGE: NO SPECIAL REQUIREMENTS.

## **EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

GENERAL CONSIDERATIONS:

CONSIDER THE POTENTIAL HAZARDS OF THIS MATERIAL (SEE HAZARDS IDENTIFICATION) APPLICABLE EXPOSURE LIMITS, JOB ACTIVITIES, AND OTHER SUBSTANCES IN THE WORK PLACE WHEN DESIGNING ENGINEERING CONTROLS AND SELECTING PERSONAL PROTECTIVE EQUIPMENT. IF ENGINEERING CONTROLS OR WORK PRACTICES ARE NOT ADEQUATE TO PREVENT

EXPOSURE TO HARMFUL LEVELS OF THIS MATERIAL, THE PERSONAL PROTECTIVE EQUIPMENT LISTED BELOW IS RECOMMENDED. THE USER SHOULD READ AND UNDERSTAND ALL INSTRUCTIONS AND LIMITATIONS SUPPLIED WITH THE EQUIPMENT SINCE PROTECTION IS USUALLY PROVIDED FOR A LIMITED TIME OR UNDER CERTAIN CIRCUMSTANCES.

ENGINEERING CONTROLS:

USE IN A WELL-VENTILATED AREA. IF USER OPERATIONS GENERATE AN OIL MIST, USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTIIATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW THE RECOMMENDED MINERAL OIL MIST EXPOSURE LIMITS.

PERSONAL PROTECTIVE EQUIPMENT:

EYE/FACE PROTECTION:

NO SPECIAL EYE PROTECTION IS NORMALLY REQUIRED.

SKIN PROTECTION:

WEAR PROTECTIVE CLOTHING IF ENGINEERING CONTROLS OR WORK PRACTICES ARE NOT ADEQUATE TO PREVENT SKIN CONTACT. SELECTION PF PROTECTIVE CLOTHWG MAY INCLUDE GLOVES, APRON, BOOTS, AND COMPLETE FACIAL PROTECTION DEPENDING ON OPERATIONS CONDUCTED. SUGGESTED MATERIALS FOR PROTECTIVE GLOVES INCLUDE: (NITRILE) (VITON) (SILVER SHIELD).

RESPIRATORY PROTECTION:

NO RESPIRATORY PROTECYION IS NORMALLY REQUIRED. IF USER OPERATIONS GENERATE AN OIL MIST, DETERMINE IF AIRBORNE CONCENTRATIONS ARE BELOW THE RECOMMENDED MINERAL OIL MIST EXPOSURE LIMITS. IF NOT WEAR A NIOSH APPROVED RESPIRATOR THAT PROVIDES ADEQUATE PROTECTION FROM MEASURED CONCENTRATIONS OF THIS MATERIAL. USE THE FOLLOWING ELEMENTS FOR AIR-PURIFYING RESPIRATORS: PARTICULATE.

## PHYSICAL AND CHEMICAL PROPERTIES

---

PHYSICAL DESCRIPTION:	GREEN GREASE
p/H:	NDA
VAPOR PRESSORE:	NDA
VAPOR DENSITY:	(AIR=1)
BOILING POINT:	NIDA
FREEZING POINT:	NDA
MELTING POINT:	NDA
SOLUBILITY:	SOLUBLE IN HYDROCARBON SOLVENTS; INSOLUBLE IN WATER.
SPECIFIC GRAVITY:	1.02 @ 15.5/15.6e
EVAPORATION RATE	NA
VISCOSITY:	-100 SUS @ 100F
PRECENT VOLATILE (VOL):	NA

## STABILITY AND REACTIVITY

---

HAZARDOUS DISCOMPOSITION PRODUCTS:

NO DATA AVAILABLE.

CHEMICAL STABILITY:

STABLE.

CONDITIONS TO AVOID:

NO DATA AVAILABLE.

INCOMPATIBILITY WITH OTHER MATERIALS:

MAY REACT WITH STRONG OXIDIZING AGENTS, SUCH AS CHLORATES, PEROXIDES, ETC.

HAZARDOUS POLYMERIZATION:

POLYMERIZATION WILL NOT OCCUR.



## FOOD CONTACT STATUS

---

USDA: U-2 STATUS: THIS PRODUCT IS ACCEPTABLE TO THE USDA FOR USE AS A LUBRICATE IN OFFICIAL MEAT AND POULTRY ESTABLISHMENTS PROVIDED THERE IS NO POSSIBILITY OF THE LUBRICANT OR LUBRICATED PART CONTACTING EDIBLE PRODUCTS.

## OTHER INFORMATION

---

NFPA RATINGS: HEALTH 1; FLAMMABILITY 1, REACTIVITY 0,  
HMIS RATINGS: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0,  
(0-LEAST, 1-SLIGHT, 2-MODERATE, 3-HIGH, 4-EXTREME, PPE; - PERSONAL PROTECTION EQUIPMENT INDEX RECOMMENDATION - CHRONIC EFFECT INDICATOR). THESE VALUES ARE OBTAINED USING THE GUIDELINES OR PUBLISHED EVALUATIONS PREPARED BY THE NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) OR THE NATIONAL PAINT AND COATING ASSOCIATION (FOR HWIS RATINGS).

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT.

TLV	- THRESHOLD LIMIT VALUE	TWA	- TIME WEIGHTED AVERAGE
STEL	- SHORT-TERM EXPOSURE LIMIT	TFQ	- THRESHOLD PLANNING QUANTITY
RQ	- REPORTABLE QUANTITY	PEL	- PERMISSIBLE EXPOSURE LIMIT
C	- CEILING LIMIT	CAS	- CHEMICAL ABSTRACT SERVICE NUMBER
AI-5	- APPENDIX A CATEGORIES	0	- CHANGE HAS BEEN PROPOSED
NDA	- NO DATA AVAILABLE	NA	- NOT APPLICABLE

---

ISSUED: SEPTEMBER 01, 2005  
SUPERSEDES: AUGUST 16, 2000

THE ABOVE INFORMATION IS BASED ON THE DATA OF WHICH WE ARE AWARE: AND IS BELIEVED TO BE CORRECT AS OF THE DATE HEREOF. SINCE THIS INFORMATION MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR AND SINCE DATA MADE AVAILABLE SUBSEQUENT TO THE DATE HEREOF MAY SUGGEST MODIFICATION OF THE INFORMATION, WE DO NOT ASSUME ANY RESPONSIBILITY FOR THE RESULTS OF ITS USE. THIS INFORMATION IS FURNISHED UPON CONDITIONS THAT THE PERSON RECEIVING IT SHALL MAKE HIS OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS PARTICULAR PURPOSE